Service Bulletin



Gas Broiler On/Off Switch Replacement Kit #8423-01R



CAUTION: Read and understand this service bulletin thoroughly before starting. Only a trained, experienced service technician should attempt this service procedure.




Figure 1 - On / Off Switch Replacement

Instructions With White Plastic Connectors

If current set up <u>includes</u> white plastic connectors, then remove old part and replace with new.

- Remove switch from front panel by squeezing the top and bottom and pushing out of the front.
- 2. Disconnect white connector and remove switch.
- Attach new switch to front panel by pushing in until it clicks.
- 4. Connect new switch to the white connector.

Instructions Without White Plastic Connectors

If current set up <u>does not include</u> white plastic connectors, follow steps to prepare for blue wire nuts.

- 1. Unscrew acorn nut and cover to get to wires.
- 2. Remove blue wire nut (2) connecting the on-off switch to the power cord and motor.
- 3. Remove switch from bracket by squeezing the top and bottom and pushing out of the front.
- 4. Prep new switch
 - a. Cut wire as close to connector as possible and remove connector.
 - b. Strip 0.5" from both wires.
- Attach new switch to bracket by pushing in until it clicks.
- 6. Make sure to do the thing that needs to be done
- 7. This will help you do the thing you are trying to do
- 8. Eventually you will have done the thing you were trying to do
- 9. Then you choose a new thing
- 10. Connect wires using blue wire nuts per wire diagram.
- 11. Fit all wires back into box and tighten cover with acorn nut.

AVOID ERROR IN PARTS SELECTION. When ordering use complete EmberGlo Part Number and Description. Furnish the Product Model Number, Bill of Material Number and Serial Number (if available) from the specification plate found on the product.

IMPORTANT: Availability of parts as well as specifications are subject to change without notice. Please consult factory for item availability.

SAFETY INFORMATION TERMS: The following terms are used to identify hazards, safety precaution of special notations and have standard meanings throughout this manual. They are printed in all capital letters using a bold type face as shown below, and preceded by the exclamation mark symbol. When you see the safety alert symbol and one of the safety information terms as shown below, be aware of the hazard potential.

DANGER: Identifies the most serious hazards which will result in severe personal injury or death.



WARNING: CAUTION:

Signifies a hazard that could result in personal injury or death. Identifies unsafe practices which would result in minor personal injury or product and property damage.





A Div of Midco® International Inc. 4140 West Victoria Street Chicago, Illinois 60646 toll free 866.705.0515

tel 773.604.8700 fax 866.580.8700 web www.emberglo.com e-mail sales@emberglo.com